



LNR5584

Linear Lighting

Standard Product Features

| | |
|----------------|--|
| Usage Area | Indoor Lighting, Bar, Restaurant, Cafe, Store, Showroom, Supermarket, Office, Education Area, Mall, Hotel, SPA, GYM, Health Center, Hospital, Sports Hall, Stadium |
| Montage | Surface Mounted, Pendant, Low Ceiling |
| Led Color | White, Amber, RGB |
| IP Class | IP20 |
| Led Type | Undefined |
| Body | Aluminum Injection |
| Diffuser | Opal Polycarbonate PMMA |
| Luminaire Size | Desired Luminaire Size |
| Driver | Eaglerise, Helvar, Osram, Philips, Tridonik |

Optical Electrical Features

| | |
|-----------------------------|-----------------------------------|
| Power Consumption | 30W, 40W, 50W |
| Luminaire Lumen | 3000LM, 4000LM, 5000LM |
| Color Temperature | 2700K, 3000K, 4000K, 5000K, 6500K |
| Angle | 30-60-90° |
| Color Rendering Index (CRI) | 80+, 90+ |

Other Features

| | |
|-----------------------------|---|
| Type/ Shape | Decorative Lighting, Rectangular Lighting |
| Highlights | Undefined |
| Operating Temperature Range | -25 / +45 |
| Led Lifetime | 100.000K |

Optional Features

Optional Features

0-10V DIM, DALI Compatibility, Kit Compatibility,
Switch DIM, Triac DIM, Tunable Compatibility

