

FLUSH MOUNTED LED PANEL

2 to

Led Panel

Standard Product Features

Usage Area	Indoor Lighting, Industrial Lighting, Bar, Restaurant, Cafe, Store, Showroom, Supermarket, Office, Education Area, Mall, Hotel, SPA, GYM, Health Center, Hospital, Sports Hall, Stadium
Montage	Flush Mounted, High Ceiling, Low Ceiling
Led Color	White, Amber, RGB
IP Class	IP40
Led Type	Undefined
Body	DKP Sheet
Diffuser	Microprismatic Lens - PMMA Opal
Luminaire Size	60cm - 80cm
Driver	Eaglerise, Helvar, Mosso, Osram, Philips, Tridonik

Optical Electrical Features

Power Consumption	30W, 40W, 45W, 50W
Luminaire Lumen	4700LM
Color Temperature	2700K, 3000K, 4000K, 5000K, 6500K
Angle	90°
Color Rendering Index (CRI)	80+

Other Features

Type/ Shape	Square Lighting
Highlights	Undefined
Operating Temperature Range	-25 / +45
Led Lifetime	60.000K

Optional Features

Optional Features

0-10V DIM, DALI Compatibility,Kit Compatibility, Switch DIM, Triac DIM, Tunable Compatibility

