



ANGLE Concealed Lighting

Concealed Lighting

Standard Product Features

Usage Area	Outdoor Lighting, Industrial Lighting, Road, Avenue, Street Lighting, Park, Garden Lighting, Building, Facade, Wall Lighting, Bar, Restaurant, Cafe, Warehouse, Factory, Production Facility, Food Lighting, Security, Store, Showroom, Supermarket, Office, Education Area, Mall, Hotel, SPA, GYM, Parking Lot, Hallway, Health Center, Hospital, Sports Hall, Stadium
Montage	Surface Mounted
Led Color	White, Amber, Red, RGB
IP Class	IP65
Led Type	Undefined
Body	Opal Polycarbonate PMMA
Diffuser	Opal Diffuser, Opal Polycarbonate PMMA
Luminaire Size	Desired Luminaire Size
Driver	Eaglerise, Helvar, Meanwell, Mosso, Osram, Philips, Tridonik

Optical Electrical Features

Power Consumption	12W
Luminaire Lumen	Undefined
Color Temperature	2700K, 3000K, 4000K, 5000K, 6500K
Angle	Undefined
Color Rendering Index (CRI)	80+

Other Features


Type/ Shape	Decorative Lighting	
-------------	---------------------	--

Highlights	Undefined
Operating Temperature Range	Undefined
Led Lifetime	60.000K

Optional Features

Optional Features	0-10V DIM, DALI Compatibility,Kit Compatibility, Switch DIM, Triac DIM, Tunable Compatibility
	emen zim, mae zim, ranazie cempatizim,







3/3