



Standard Product Features

| Usage Area | Indoor Lighting, Industrial Lighting, Bar, Restaurant, Cafe, Warehouse, Factory, Production Facility, Food Lighting, Store, Showroom, Supermarket, Office, Education Area, Mall, Hotel, SPA, GYM, Health Center, Hospital, Sports Hall, Stadium |
|----------------|---|
| Montage | Rail Type |
| Led Color | White, Amber, RGB |
| IP Class | IP20 |
| Led Type | Undefined |
| Body | Aluminum Injection |
| Diffuser | Aluminum Reflector |
| Luminaire Size | Desired Luminaire Size |
| Driver | Eaglerise, Helvar, Meanwell, Osram, Philips, Tridonik |

Optical Electrical Features

| Power Consumption | 30W, 40W |
|-----------------------------|-----------------------------------|
| Luminaire Lumen | 4000LM, 4500LM |
| Color Temperature | 2700K, 3000K, 4000K, 5000K, 6500K |
| Angle | 20-30-40-60° |
| Color Rendering Index (CRI) | 80+ |

Other Features

| Type/ Shape | Spot Lighting |
|-----------------------------|---------------|
| Highlights | Undefined |
| Operating Temperature Range | Undefined |

1/3

Led Lifetime 100.000K

Optional Features

Optional Features

0-10V DIM, DALI Compatibility,Kit Compatibility, Switch DIM, Triac DIM, Tunable Compatibility





