



## **Standard Product Features**

| Usage Area     | Indoor Lighting, Bar, Restaurant, Cafe, Warehouse, Factory, Production Facility, Food Lighting, Store, Showroom, Supermarket, Office, Education Area, Mall, Hotel, SPA, GYM, Health Center, Hospital, |
|----------------|---|
| Montage        | Rail Type   |
| Led Color      | White, Amber, RGB   |
| IP Class       | IP20  |
| Led Type       | Undefined   |
| Body           | Aluminum Injection  |
| Diffuser       | Glare Controlled Optical Lens   |
| Luminaire Size | Desired Luminaire Size  |
| Driver         | Eaglerise, Helvar, Meanwell, Osram, Philips, Tridonik   |

## **Optical Electrical Features**

| Power Consumption           | 15W, 30W                          |
|-----------------------------|-----------------------------------|
| Luminaire Lumen             | 1000LM, 2000LM, 2500LM            |
| Color Temperature           | 2700K, 3000K, 4000K, 5000K, 6500K |
| Angle                       | 15-30-45°                         |
| Color Rendering Index (CRI) | 80+                               |

## **Other Features**

| Type/ Shape                 | Spot Lighting |
|-----------------------------|---------------|
| Highlights                  | Undefined     |
| Operating Temperature Range | Undefined     |
| Led Lifetime                | 60.000K       |

## **Optional Features**

**Optional Features** 

0-10V DIM, DALI Compatibility,Kit Compatibility, Switch DIM, Triac DIM, Tunable Compatibility