



## CRATER

### Ray Spot Lighting

## Standard Product Features

Usage Area	Indoor Lighting, Industrial Lighting, Bar, Restaurant, Cafe, Warehouse, Factory, Production Facility, Food Lighting, Store, Showroom, Supermarket, Office, Education Area Mall, Hotel, SPA, GYM, Health Center, Hospital, Sports Hall, Stadium
Montage	Rail Type, Low Ceiling
Led Color	White, Amber, RGB
IP Class	IP20
Led Type	<b>Undefined</b>
Body	Aluminum Injection
Diffuser	Aluminum Reflector
Luminaire Size	Desired Luminaire Size
Driver	Eaglerise, Helvar, Meanwell, Mosso, Osram, Philips, Tridonik

## Optical Electrical Features

Power Consumption	30W, 40W
Luminaire Lumen	2000LM, 3000LM
Color Temperature	2700K, 3000K, 4000K, 5000K, 6500K
Angle	90°
Color Rendering Index (CRI)	80+

## Other Features

Type/ Shape	Spot Lighting
Highlights	<b>Undefined</b>
Operating Temperature Range	-25 / +55

Led Lifetime

100.000K

## Optional Features

Optional Features

0-10V DIM, DALI Compatibility, Kit Compatibility,  
Switch DIM, Triac DIM, Tunable Compatibility

