



Standard Product Features

Usage Area	Indoor Lighting, Industrial Lighting, Bar, Restaurant, Cafe, Warehouse, Factory, Production Facility, Food Lighting, Store, Showroom, Supermarket, Office, Education Area, Mall, Hotel, SPA, GYM, Health Center, Hospital, Sports Hall, Stadium
Montage	Flush Mounted, Low Ceiling
Led Color	White, Amber, RGB
IP Class	IP20
Led Type	Undefined
Body	DKP Sheet
Diffuser	Glare Controlled Optical Lens
Luminaire Size	Desired Luminaire Size
Driver	Eaglerise, Helvar, Meanwell, Osram, Philips, Tridonik

Optical Electrical Features

Power Consumption	15W, 25W
Luminaire Lumen	2000LM, 2500LM
Color Temperature	2700K, 3000K, 4000K, 5000K, 6500K
Angle	20-30-40-60°
Color Rendering Index (CRI)	80+,90+

Other Features

Type/ Shape	Decorative Lighting, Spot Lighting
Highlights	Undefined
Operating Temperature Range	Undefined

Led Lifetime

100.000K

Optional Features

Optional Features

0-10V DIM, DALI Compatibility,Kit Compatibility, Switch DIM, Triac DIM, Tunable Compatibility

