



## NORMA

### Ray Spot Lighting

## Standard Product Features

Usage Area	Indoor Lighting, Bar, Restaurant, Cafe, Warehouse, Factory, Production Facility, Food Lighting, Store, Showroom, Supermarket, Office, Education Area Mall, Hotel, SPA, GYM, Health Center, Hospital, Sports Hall, Stadium
Montage	Surface Mounted, Pendant, Rail Type, Low Ceiling
Led Color	White, Amber, RGB
IP Class	IP40
Led Type	<b>Undefined</b>
Body	Aluminum Injection
Diffuser	Aluminum Reflector, Opal Polycarbonate PMMA
Luminaire Size	Desired Luminaire Size
Driver	Eaglerise, Helvar, Mosso, Osram, Philips, Tridonik

## Optical Electrical Features

Power Consumption	20W, 30W, 40W, 75W, 100W
Luminaire Lumen	5000LM, 6000LM, 7000LM
Color Temperature	2700K, 3000K, 4000K, 5000K, 6500K
Angle	90°
Color Rendering Index (CRI)	80+

## Other Features

Type/ Shape	Decorative Lighting, Rectangular Lighting, Spot Lighting
Highlights	<b>Undefined</b>
Operating Temperature Range	<b>Undefined</b>

Led Lifetime

100.000K

## **Optional Features**

Optional Features

0-10V DIM, DALI Compatibility,Kit Compatibility,  
Switch DIM, Triac DIM, Tunable Compatibility

