



PICTOR87x87

Linear Lighting

Standard Product Features

Usage Area	Indoor Lighting, Bar, Restaurant, Cafe, Store, Showroom, Supermarket, Office, Education Area, Mall, Hotel, SPA, GYM, Health Center, Hospital, Sports Hall, Stadium
Montage	Surface Mounted, Pendant
Led Color	White, Amber, RGB
IP Class	IP20
Led Type	Undefined
Body	Aluminum Injection
Diffuser	Opal Polycarbonate PMMA - Prismatic Lens
Luminaire Size	Desired Luminaire Size
Driver	Eaglerise, Helvar, Osram, Philips, Tridonik

Optical Electrical Features

Power Consumption	30W, 40W, 50W, 60W, 80W
Luminaire Lumen	3000LM, 4000LM, 5000LM, 6000LM
Color Temperature	2700K, 3000K, 4000K, 5000K, 6500K
Angle	30-60-90°
Color Rendering Index (CRI)	80+, 90+

Other Features

Type/ Shape	Decorative Lighting, Rectangular Lighting
Highlights	Undefined
Operating Temperature Range	-25 / +45
Led Lifetime	100.000K

Optional Features

Optional Features

0-10V DIM, DALI Compatibility, Kit Compatibility,
Switch DIM, Triac DIM, Tunable Compatibility

