



LNR-SPT-LG

Magnet Lighting

Standard Product Features

Usage Area	Indoor Lighting, Bar, Restaurant, Cafe, Food Lighting, Store, Showroom, Supermarket, Office, Education Area, Mall, Hotel, SPA, GYM, Health Center, Hospital, Sports Hall, Stadium
Montage	Surface Mounted, Pendant, Rail Type
Led Color	White, Amber, RGB
IP Class	IP20, IP40
Led Type	Undefined
Body	Aluminum Extrusion
Diffuser	Opal Polycarbonate PMMA
Luminaire Size	Desired Luminaire Size
Driver	Eaglerise, Helvar, Osram, Philips, Tridonik

Optical Electrical Features

Power Consumption	10W, 15W
Luminaire Lumen	700LM, 750LM
Color Temperature	2700K, 3000K, 4000K, 5000K, 6500K
Angle	20-30-40°
Color Rendering Index (CRI)	80+, 90+

Other Features

Type/ Shape	Spot Lighting, Magnet
Highlights	Undefined
Operating Temperature Range	-25 / +55
Led Lifetime	100.000K, 60.000K

Optional Features

Optional Features

0-10V DIM, DALI Compatibility, Kit Compatibility,
Switch DIM, Triac DIM, Tunable Compatibility

