



# **Linear Lighting - Street Lighting Systems**

**Street Lighting** 

### **Standard Product Features**

Usage Area	Outdoor Lighting, Road, Avenue, Street Lighting, Park, Garden Lighting, Building, Facade, Wall Lighting, Warehouse, Factory, Production Facility, Parking Lot, Hallway
Montage	Floor
Led Color	White, Amber, RGB
IP Class	IP66
Led Type	Undefined
Body	Aluminum Extrusion
Diffuser	Glare Controlled Optical Lens
Luminaire Size	Desired Luminaire Size
Driver	Eaglerise, Helvar, Meanwell, Osram, Philips, Tridonik

## **Optical Electrical Features**

Power Consumption	30W, 50W, 60W, 80W, 100W, 120W
Luminaire Lumen	4000LM, 6500LM, 7750LM, 13000LM, 15000LM
Color Temperature	2700K, 3000K, 4000K, 5000K, 6500K
Angle	15-30-45°, Desired Angle
Color Rendering Index (CRI)	80+

### **Other Features**

Type/ Shape	Lighting Pole
Highlights	Undefined
Operating Temperature Range	Undefined
Led Lifetime	60.000K

## **Optional Features**

**Optional Features** 

0-10V DIM, DALI Compatibility,Kit Compatibility, Switch DIM, Triac DIM, Tunable Compatibility

